

SENCITY® Urban 300

1399.31.0019

Properties

- Low PIM directional MIMO 2x2 antenna for small cell, indoor/outdoor DAS applications
- Supports MIMO 2x2 in 4G and 5G Bands
- Supports the frequency range from 698-960 MHz, 1695-2700 MHz, 3100-4200 MHz.
- Suitable for outdoor use
- Plenum rated cable terminated with 4310 female connector

**Electrical bands**

	Band 1	Band 2	Band 3
Name	Cellular	Cellular	Cellular
Frequency	698 MHz ... 960 MHz	1695 MHz ... 2700 MHz	3100 MHz ... 4200 MHz
Impedance	50 Ω	50 Ω	50 Ω
VSWR	1.8	1.7	1.6
Gain	5 dBi	7 dBi	6.5 dBi
HPBW vertical	85 °	65 °	65 °
HPBW horizontal	85 °	70 °	65 °
Isolation between Ports	18 dB	25 dB	22 dB
Ambient Temperature	25 °C	25 °C	25 °C
Composite Power max	50 W	50 W	50 W

Ports

	Port 1	Port 2
Port name	Cellular 1	Cellular 2
Connector	4.3-10, jack (female)	4.3-10, jack (female)
Cable media type	Sucoform_141-CU-CMP	Sucoform_141-CU-CMP
Polarization	+45° slant	-45° slant
DC grounded	No	No

SENCITY® Urban 300

1399.31.0019

Connections		
Port number	Port 1	Port 2
Band 1	✓	✓
Band 2	✓	✓
Band 3	✓	✓

Mechanical data	
Weight	1.1 kg
Dimensions	260 mm x 200 mm x 90 mm (Height x Width x Depth)

Interface and material data	
Radome material	PC (Polycarbonate)
Radome colour	RAL 7035 (light gray)

Environmental data	
Operation temperature	-40 °C ... 70 °C
Installation temperature	-40 °C ... 70 °C
Storage temperature	-40 °C ... 70 °C
Environment (application)	Indoor/Outdoor
Ingress protection (IP Rating)	IP67

Additional Information
Wall bracket is included in the package. Bracket for pole installation is a separate item (9091.99.0292)

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P35384 / Date of publication: 30.04.2024 / uncontrolled copy